

WHAT IS CLAIMED IS:

1. Electronic equipment, comprising:

a main body;

a first recording medium receiving unit disposed in the main body, the first recording medium receiving unit selectively providing an enabling state, which enables a first recording medium to be loaded or unloaded into or from the first recording medium receiving unit, and a disabling state, which disables the first recording medium from being loaded or unloaded thereinto or therefrom; and

a second recording medium receiving unit disposed in the main body, the second recording medium receiving unit being movable between an enabling position, which enables a second recording medium to be loaded or unloaded into or from the second recording medium receiving unit, and a disabling position, which disables the second recording medium from being loaded or unloaded thereinto or therefrom,

wherein the first recording medium receiving unit is placed in the enabling state when the second recording medium receiving unit moves to the enabling position, and the first recording medium receiving unit is placed in the disabling state when the second recording medium receiving unit moves to the disabling position.

2. The electric equipment as claimed in claim 1, wherein the second recording medium receiving unit has a slot through which the second recording medium is to be loaded or unloaded into or from the second recording medium receiving unit, said slot being exposed out of the main body when the second recording medium receiving unit moves to the enabling position.

3. The electric equipment as claimed in claim 1, wherein the first recording medium receiving unit has a slot through which the first recording medium is to be loaded or unloaded into or from the first recording medium receiving unit; and

wherein the second recording medium receiving unit is movable between a slot concealing position in which the slot is concealed and a slot exposing position in which the slot is exposed out of the main body, the second recording medium being disabled from being loaded or unloaded into or from the second recording medium receiving unit, when the second recording medium receiving unit is placed in the slot concealing position, and the second recording medium being enabled to be loaded or unloaded thereinto or therefrom, when the second recording medium receiving unit is placed in the slot exposing position.